



Technical Section: Vibration and Shock Isolation

www.vibrationmounts.com Phone: 516.328.3662 Fax: 516.328.3365

Table of Contents

| | |
|---|-------|
| 1.0 FUNDAMENTALS OF VIBRATION AND SHOCK | |
| 1.1 What Is Vibration? | T1-2 |
| 1.1.1 Damping | T1-2 |
| 1.2 What is Shock? | T1-3 |
| 1.3 What is Noise? | T1-3 |
| 1.4 Principles of Vibration Isolation | T1-4 |
| 1.5 Principles of Noise Reduction | T1-5 |
| 2.0 BASIC DEFINITIONS AND CONCEPTS IN VIBRATION AND SHOCK ANALYSIS | |
| 2.1 Kinematic Characteristics | T1-5 |
| 2.2 Rigid-Body Characteristics | T1-6 |
| 2.3 Spring and Compliance Characteristics | T1-6 |
| 2.4 Damping, Friction and Energy-Dissipation Characteristics | T1-7 |
| 2.5 Vibration Characteristics of Mechanical Systems | T1-7 |
| 2.5.1 Amplitude-Frequency Characteristics of Forced Vibrations | T1-8 |
| 3.0 VIBRATION ISOLATION | T1-9 |
| 3.1 Vibration Isolation of Vibration-Producing Products | T1-10 |
| 3.2 Vibration Isolation of Vibration-Sensitive Objects | T1-12 |
| 3.3 Shock Isolation | T1-14 |
| 3.3.1 Shock Motion of Base (Base Suddenly Stops or Accelerates) | T1-16 |
| 3.3.2 Sudden Impact on Equipment | T1-17 |
| 4.0 NONLINEARITIES | T1-17 |
| 5.0 MULTIDEGREE OF FREEDOM SYSTEMS, COUPLED MODES | T1-19 |
| 6.0 STATIC LOAD DISTRIBUTION CALCULATION | T1-20 |
| 6.1 Advantages of CNF Vibration Isolators | T1-21 |
| 7.0 CONNECTIONS OF SPRING ELEMENTS | T1-22 |
| 7.1 Springs in Parallel | T1-22 |
| 7.2 Springs in Series | T1-22 |
| 7.3 Spring Connected Partly in Parallel and Partly in Series | T1-22 |
| 8.0 3-D OBJECT DRIVEN BY VIBRATORY FORCE AND TORQUES | T1-23 |
| 8.1 Displacement of the Object | T1-23 |
| 8.2 Undamped Natural Frequencies | T1-24 |
| 8.3 Mount Deflections | T1-24 |
| 9.0 COMPLEX DRIVING FORCES | T1-25 |
| 10.0 DESIGN PROBLEM EXAMPLES | T1-26 |
| REFERENCES | T1-34 |
| APPENDIX | |
| 1 Useful Formulas in Vibration Analysis | T1-35 |
| 2 Properties of Rubber and Plastic Materials | T1-37 |
| 3 Hardness Conversion Charts | T1-38 |