



Technical Section: Shaft Couplings

www.vibrationmounts.com Phone: 516.328.3662 Fax: 516.328.3365

Table of Contents

1.0 INTRODUCTION

2.0 APPLICATION CONSIDERATIONS

2.1	Torque and Horsepower	T2-2
2.2	Shaft Misalignment	T2-2
2.3	Lateral and Axial Flexibility of Couplings	T2-3
2.4	Torsional Flexibility	T2-3
2.5	Backlash	T2-3
2.6	Rotational Velocity Error	T2-3
2.7	Service Conditions	T2-3

3.0 GENERAL CLASSIFICATION OF COUPLINGS AND THEIR PERFORMANCE CHARACTERISTICS

3.1	Rigid Couplings	T2-4
3.2	Misalignment-Compensating Couplings	T2-5
3.2.1	Selection Criterion for Frictional Misalignment-Compensating Couplings	T2-5
3.2.1a	Oldham Couplings	T2-5
3.2.1b	Universal or U-joints	T2-6
3.2.1b.1	General	T2-6
3.2.1b.2	Kinematics	T2-7
Example 1:	Determining the Maximum Inertia Torque	T2-7
3.2.1b.3	Joint Selection (Torque Rating)	T2-9
Example 2:	Universal Joint Selection for Continuous Operation	T2-9
Example 3:	Universal Joint Selection for Intermittent Operation with Shock Loading	T2-9
Example 4:	Determining the Maximum Speed of an Input Shaft	T2-9
3.2.1b.4	Secondary Couples	T2-10
3.2.1b.5	Joints in Series	T2-10
Example 5:	Determining the Maximum Speed of an Input Shaft in a Series	T2-10
Example 6	T2-11
3.2.2	Selection Criterion for Misalignment-Compensating Couplings with Elastic Connectors	T2-11
3.2.2.1	Designs of Elastic Misalignment-Compensating Couplings	T2-11
3.3	Torsionally Flexible Couplings and Combination Purpose Couplings	T2-12
3.3.1	Torsionally Flexible Couplings	T2-12
3.3.2	Combination Purpose Couplings	T2-13
3.3.2.1	Miscellaneous Combination Purpose Couplings	T2-15
3.3.2.1a	Flexible Shafts	T2-15
3.3.2.1b	Uniflex Couplings	T2-15
3.3.2.1c	Jaw and Spider Couplings	T2-16
3.3.2.1d	Sleeve Type Couplings (Geargrip)	T2-17

4.0	REFERENCES	T2-17
-----	------------------	-------