



# Hourglass Mounts – To 102 kgf

www.vibrationmounts.com Phone: 516.328.3662 Fax: 516.328.3365

- **MATERIAL:** Fasteners – Steel, Zinc Plated  
Isolator – Natural Rubber / Styrene-Butadiene Rubber Compound, 60 ± 5 Durometer
- **FOR COMPRESSION LOADS OF 3 TO 102 kgf (6.61 TO 225 lb.)**
- **FOR SHEAR LOADS OF 0.8 TO 8.2 kgf (1.76 TO 18.1 lb.)**



Cylindrical Mounts

## Metric

Catalog Number	M Thread Size	A Diameter mm (in.)	B Length mm (in.)	D Diameter mm (in.)	L <sub>m</sub> Stud Length mm (in.)	Maximum Load kgf (lb.)	
						Compression	Shear
V12Z09MMM121510	M4	12 (.47)	15 (.59)	7 (.28)	10 (.39)	3 (6.61)	0.8 (1.76)
V12Z09MMM252018	M6	25 (.98)	20 (.79)	10 (.39)	18 (.71)	51 (112)	3 (6.61)
V12Z09MMM302023	M8	30 (1.18)	20 (.79)	24 (.94)	23 (.91)	61 (134)	10.2 (22.5)
V12Z09MMM403020		40 (1.57)	30 (1.18)	19 (.75)	20 (.79)	62 (137)	6.1 (13.4)
V12Z09MMM403020L		40 (1.57)	30 (1.18)	27 (1.06)	20 (.79)	102 (225)	8.2 (18.1)

NOTE: Dimensions in ( ) are inch.