



Foot Mounts – Cylindrical Type

www.vibrationmounts.com Phone: 516.328.3662 Fax: 516.328.3365

- **MATERIAL:** Isolator – Neoprene
Screw & Plate – Steel, Zinc Plated



Metric

FEATURES:

- Compared to the same cylindrical vibration mounts, the spring rate is smaller for better vibration and noise isolation.
- The contact surface has a special pattern for stable contact with the floor.
- Since there are no anchor bolts, the equipment can be rearranged easily.

APPLICATIONS

- PARTS FEEDERS
- OFFICE EQUIPMENT
- PRECISION MACHINERY
- MEASURING EQUIPMENT
- ELECTRONIC EQUIPMENT
- OPTICAL EQUIPMENT
- TEST EQUIPMENT

NOTE: Dimensions in () are inch.

Catalog Number	D	L	l	d	t	Load kgf (lb.)	Max. Allowable Load kgf (lb.)	Spring Rate kgf/cm (lb./in.)	Ratio Kx/Kz
V11Z57MKN020	20 (.79)	11 (.43)	15 (.59)	M6	2 (.08)	12 (26.5)	16 (35.3)	85 (476)	.19
V11Z57MKN030	30 (1.18)	15 (.59)	18 (.71)	M8	2.3 (.09)	22 (48.5)	35 (77.2)	110 (616)	.20
V11Z57MKN040	40 (1.57)	20 (.79)				50 (110.2)	75 (165.3)	190 (1064)	.22
V11Z57MKN050	50 (1.97)	25 (.98)	25 (.98)	M10	3.2 (.13)	75 (165.3)	120 (264.6)	280 (1568)	.19

7
Bumpers & Feet