



- **MATERIAL:** Molded Polyurethane (Pressure-Sensitive), Self-Adhesive

MOUNTING INSTRUCTIONS:

To obtain a maximum bond, surfaces need to be smooth, nonporous, clean, dry and free of all debris, oils and solvents. Clean the surface with a low strength solvent such as isopropyl alcohol (rubbing alcohol) or heptane. Follow solvent manufacturer's precautionary warnings and suggested handling procedures when using solvents. Bend pad slightly grasping bumper on sides without touching the adhesive. Apply with enough pressure to ensure a complete bond. Allow a dwell time of 24 hours before exposing to heavy force or weight. The composition of this product contains no migratory plasticizers of any kind which would mar surfaces of contact.

APPLICATIONS

- CABINETS
- PICTURE FRAMES
- DOORS AND WINDOWS
- APPLIANCES
- ELECTRONICS
- FURNITURE
- TROPHIES
- OFFICE EQUIPMENT
- BOATING
- AUTOMOTIVE
- KITCHEN EQUIPMENT


FEATURES:

- Easy peel and stick application.
- Nonstaining and nonmarring.
- High coefficient of friction.
- Superb resistance to skidding.
- Vibration and shock damping.
- Crack-resistant and resilient.
- Low abrasion.
- UL recognized components.
- Shelf life – 24 months, based on accelerated aging.
- Storage – +73°F (+23°C) and 55% relative humidity.

Cylindrical Type

Priced Per Sheet

Catalog Number		D Diameter	H Height	No. of pieces per sheet
Clear	Black			
V10R83-C03712	V10R83-B03712	.375 (9.5)	.125 (3.2)	300
V10R83-C03719	V10R83-B03719		.190 (4.8)	
V10R83-C05006	V10R83-B05006		.060 (1.5)	
V10R83-C05014	V10R83-B05014	.500 (12.7)	.140 (3.5)	200
* V10R83-C05014SD	—		.250 (6.4)	
V10R83-C05025	V10R83-B05025		.400 (10.2)	
V10R83-C06540	V10R83-B06540	.750 (19.1)	.160 (4.1)	98
V10R83-C07516	V10R83-B07516	.780 (19.8)	.200 (5.1)	84
V10R83-C08112	V10R83-B08112	.810 (20.6)	.120 (3)	72
V10R83-C12310	V10R83-B12310	1.230 (31.24)	.100 (2.54)	32



*SD = Soft 50-55 durometer; soft durometer bumpers are not recommended for load bearing applications.
NOTE: Dimensions in () are mm.

Continued on the next page

Bumpers




www.vibrationmounts.com Phone: 516.328.3662 Fax: 516.328.3365

- **MATERIAL:** Molded Polyurethane (Pressure-Sensitive), Self-Adhesive

Dome Type

Priced Per Sheet

Catalog Number		D Diameter	H Height	No. of pieces per sheet
Clear	Black			
V10R84-C02506	V10R84-B02506	.250 (6.4)	.062 (1.6)	578
V10R84-C02507	V10R84-B02507		.079 (2.1)	
V10R84-C03108	V10R84-B03108	.312 (7.9)	.085 (2.2)	450
V10R84-C03308	V10R84-B03308	.335 (8.5)		
* V10R84-C03308SD	—			
* V10R84-C03715SD	—	.375 (9.5)	.150 (3.8)	200
V10R84-C03715	V10R84-B03715		.211 (5.4)	300
V10R84-C03721	V10R84-B03721			
V10R84-C04420	V10R84-B04420	.440 (11.1)	.200 (5.1)	242
V10R84-C06231	V10R84-B06231	.620 (15.7)	.310 (7.9)	128
V10R84-C07038	V10R84-B07038	.700 (17.78)	.380 (9.6)	98
V10R84-C07507	V10R84-B07507	.750 (19.1)	.075 (1.9)	84



*SD = Soft 50-55 durometer; soft durometer bumpers are not recommended for load bearing applications.

7

Bumpers & Feet


Conical Type

Priced Per Piece

Catalog Number		D Diameter	H Height	No. of pieces per sheet
Clear	Black			
V10R85-C07256	V10R85-B07256	.720 (18.3)	.560 (14.2)	1
V10R85-C07575	V10R85-B07575	.750 (19.1)	.750 (19.1)	
V10R85-C07988	V10R85-B07988	.787 (20)	.886 (22.5)	

NOTE: Dimensions in () are mm.

Continued on the next page






- **MATERIAL:** Molded Polyurethane (Pressure-Sensitive), Self-Adhesive

Recessed Type

Priced Per Sheet


Catalog Number		D Diameter	H Height	No. of pieces per sheet
Clear	Black			
V10R86-C08840	V10R86-B08840	.880 (22.3)	.400 (10.2)	72
V10R86-C18160	V10R86-B18160	1.810 (46)	.600 (15.2)	1



Square Type

Priced Per Sheet

Catalog Number		L Side	H Height	No. of pieces per sheet
Clear	Black			
V10R87-C04010	V10R87-B04010	.400 (10.2)	.100 (2.5)	242
V10R87-C05012	V10R87-B05012	.500 (12.7)	.120 (0.3)	200
V10R87-C05023	V10R87-B05023		.230 (5.8)	
V10R87-C07825	V10R87-B07825	.780 (19.8)	.250 (6.4)	98
V10R87-C07838	V10R87-B07838		.380 (9.7)	1
V10R87-C08130	V10R87-B08130	.810 (20.6)	.300 (7.6)	98
V10R87-C10018	V10R87-B10018	1.000 (25.4)	.180 (4.6)	55



NOTE: Dimensions in () are mm.