



SORBO – Pads – Sorbothane®

www.vibrationmounts.com Phone: 516.328.3662 Fax: 516.328.3365

- **MATERIAL:** Sorbothane® Polyether-Based Polyurethane



APPLICATIONS

- ELECTRONICS
- GASKET MATERIAL
- SHOCK PROTECTIONS

Catalog Number	Durometer	Sheet Dimensions						Thickness Tolerance		Pressure Sensitive Adhesive	Load Rating	
		W		L		T		in.	mm		psi	kgf/cm ²
		in.	mm	in.	mm	in.	mm					
V10R13-04060044	40									NO	370	26
V10R13-04060045	50	4	101.6	6	152.4	.04	1.02	±.007	±0.18		550	38.7
V10R13-04060047	70										1100	77.3
V10R13-04060064	40									NO	180	12.7
V10R13-04060065	50	4	101.6	6	152.4	.06	1.52	±.007	±0.18		250	17.6
V10R13-04060067	70										500	35.2
V10R13-06120104A	40									YES	60	4.2
V10R13-06120105A	50	6	152.4	12	304.8	1/10	2.54	±.015	±0.38		90	6.3
V10R13-06120107A	70										180	12.7
V10R13-06120124A	40									YES	45	3.2
V10R13-06120125A	50	6	152.4	12	304.8	1/8	3.18	±.020	±0.51		60	4.2
V10R13-06120127A	70										120	8.4
V10R13-12120124	40									NO	45	3.2
V10R13-12120125	50	12	304.8	12	304.8	1/8	3.18	±.020	±0.51		60	4.2
V10R13-12120127	70										120	8.4
V10R13-12120184	40									NO	25	1.8
V10R13-12120185	50	12	304.8	12	304.8	3/16	4.76	±.020	±0.51		30	2.1
V10R13-12120187	70										60	4.2
V10R13-12120254	40									NO	15	1.1
V10R13-12120255	50	12	304.8	12	304.8	1/4	6.35	±.025	±0.64		20	1.4
V10R13-12120257	70										40	2.8
V10R13-12120504	40									NO	7	0.5
V10R13-12120505	50	12	304.8	12	304.8	1/2	12.7	±.035	±0.89		10	0.7
V10R13-12120507	70										20	1.4
V10R13-12121004	40									NO	5	0.4
V10R13-12121005	50	12	304.8	12	304.8	1	25.4	±.060	±1.52		8	0.6
V10R13-12121007	70										15	1.1